

IntelliControl[®]ICS

INTEGRATED CONTROL SOLUTIONS

DATA SHEET



MODULAR MULTIZONE RECEIVER

GXR2

GXR2

MODULAR MULTI-ZONE RECEIVER

110 VOLT FG01174
220 VOLT FG01190

FEATURES

- **Modular MultiZone Receiver** distributes up to six sources to six zones
- **Built-in High Current 12-channel Amplifier** delivers 55 watts per channel RMS @ 8 ohm and 85 watts per channel @ 4 ohm to each of six zones
- **Integrated Six Slot Card Cage** accepts any combination of up to six IntelliControl ICS integration modules
- **Plug and Play Integration** of IntelliControl ICS integration modules
- **Reliable "One Touch to Music"** operation using IntelliControl ICS Touch Screens, Keypads and remote controls
- **Party Mode** turns on all your favorite areas from any keypad or remote control
- **Global Off** turns off all areas from any keypad or remote control
- **Tone Controls** fine tune bass and treble in each separate zone
- **Balance Control** fine tunes channel levels in each separate zone
- **Programmable Turn-On Volume** for each zone
- **Alarm Clock and Sleep Timer** for each zone
- **Paging/Doorbell Input** enables system wide voice announcements from a phone system or doorbell sounds from the Niles DBI-1
- **Zone Linking** allows a grouping of zones to be controlled as a single zone. Turn-On, Source selection, Paging and Turn-Off all work in unison, yet each zone has independent volume adjustment and muting
- **Home Theater Integration Ports** enable audio and video source components shared with the home theater system to be turned on, controlled via IR and turned off as needed

- **Selectable Fixed/Variable Zone Preamp Outputs** with 12 Volt Triggers for external amplifier applications
- **Source Matching Gain Control** ensures changing sources doesn't require changing volume control settings
- **Removable Speaker Connectors** hold up to 12-gauge speaker wire
- **Expandable up to 30 Zones** with additional GXR2s
- Includes Rack Mount Kit and hardware

SPECIFICATIONS

- Agency certifications:
FG01174: Class 2/SELV covering US, Canadian and EU markets
FG01190: Safety: UL/EN 60065
 EMC: CE, CTICK
- 55 watts x 12 channels
- Frequency response: 26-20 kHz +/- 3 db
- Signal to Noise: > = 85 db
- Power supply:
FG01174: AC 120V, 60Hz
FG01190: AC 240V, 50Hz
- Power consumption: 1500 watts maximum

DIMENSIONS

- 17-3/8" wide x 5-3/4" high (including feet) x 18" deep

WARRANTY AND SHIPPING

- Warranty: Two year limited
- Shipping: Weight: 54 lbs

E N G I N E E R E D B Y



©2007 Niles Audio Corporation 12331 S.W. 130 Street, Miami, FL 33186 Tel: 800.BUY.HIFI – www.nilesaudio.com – All rights reserved. Niles, the Niles logos, IntelliControl and IntelliFile are registered trademarks of Niles Audio Corporation. All other trademarks are the property of their respective owners. Designed and engineered in the USA. 03/07 LT00225B